

BAJAK'S ROOF COATING 58810B

Description: BAJAK ROOF COATING 58810B is a high-build acrylic coating. It forms a durable elastomeric membrane with excellent flexibility and water-proofing properties. The appearance is slightly textured.

Area of use: **Exterior:** Roofs and walls.

Substrates: Concrete, masonry, woodwork, tiles, steel, PU foam, etc.

PHYSICAL CONSTANTS:

| | | | |
|-----------------------------|--|----------------|---------------|
| Colour/Shade nos: | White/10000 | | |
| Finish: | Semi-flat | | |
| Volume Solids, %: | 37±2% | | |
| Theoretical spreading rate: | 2.5 m ² /litre at 150 micron* | | |
| Flash point: | >66°C | | |
| Specific gravity: | 1.27 kg/litre | | |
| Dry to touch: | 6 hours (10°C) | 3 hours (20°C) | 1 hour (40°C) |

***The theoretical spreading rate** has been calculated for the stated volume solids and dry film thickness.

A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor.

The physical constants are subject to normal manufacturing tolerances. Further reference is made to "Explanatory Notes".

APPLICATION DETAILS:

| | | | |
|--------------------------------|-------------------|--------------------|------------------|
| Application method: | Brush/roller | Conventional spray | Airless spray |
| Thinner (max. vol.): | None | None | None |
| Cleaning of tools: | Fresh water | | |
| Indicated film thickness, dry: | 150 micron | | |
| Indicated film thickness, wet: | 400 micron | | |
| Recoat interval, min: | 6-12 hours (10°C) | 3-6 hours (20°C) | 1-3 hours (40°C) |
| Recoat interval, max: | None | None | None |

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, Sealer/primer, laitance, dirt, grease and oil. It is recommended to apply a primer/sealer prior to the specified filling procedure. Touch-up with primer/sealer on areas repaired with filler is recommended prior to application of topcoats.

Fillings: Mix 2-3 parts of sand to 1 part of BAJAK'S ROOF COATING 81540 to fill small cracks in the concrete. For large holes and cracks, BAJAK'S EPOXY GROUT 93026 is recommended.

Sealing:
On concrete: BAJAK'S ACRYLIC PRIMER/SEALER 26600.
On ferrous metal: BAJALIN PRIMER 12210.

Remarks: Use only where application and drying can proceed at temperatures above 5°C, preferably above 10°C. Drying data given is on the assumption that proper ventilation is provided.

Note: **BAJAK'S ROOF COATING 58810B is for professional use only.**

Safety: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult BAJAK Material Safety Data Sheets and follow all local or national Safety regulations. Harmful or fatal if swallowed; immediately seek medical assistance if swallowed. Avoid inhalation of possible solvent vapors or paint mist, as well as paint contact with skin and eyes. Apply only in well ventilated areas and ensure that adequate forced ventilation exists when applying paint in confined spaces or when the air is stagnant. Always take precautions against the risks of fire and explosions.

Issued: May 2016